

OsmoBSC - Feature #4393

Circuit Switched Data (CSD) Support

02/13/2020 07:55 PM - laforge

Status: New	Start date: 02/13/2020
Priority: Low	Due date:
Assignee:	% Done: 0%
Category:	
Target version:	
Spec Reference:	
Description The BSC doesn't have to do much to support CSD: <ul style="list-style-type: none">• parse the bearer service details from the 48.008 A signaling side (ASSIGNMENT CMD)• encode the bearer service details to the 48.058 Abis RSL signaling side (RSL CHAN ACT)• instruct the MGW to use RTP payload-type 120 as "CLEARMODE/8000"	
Related issues:	
Related to OsmoBTS - Feature #1572: Circuit Switched Data (CSD) Support	New 02/23/2016
Related to OsmoMSC - Feature #4394: Circuit Switched Data (CSD) Support	New 02/13/2020
Related to OsmoMGW - Feature #4395: Circuit Switched Data (CSD) Support	New 02/13/2020

History

#1 - 02/13/2020 07:55 PM - laforge

- Related to Feature #1572: Circuit Switched Data (CSD) Support added

#2 - 02/13/2020 07:57 PM - laforge

- Related to Feature #4394: Circuit Switched Data (CSD) Support added

#3 - 02/13/2020 07:59 PM - laforge

- Related to Feature #4395: Circuit Switched Data (CSD) Support added