

OsmoMSC - Feature #4394

Circuit Switched Data (CSD) Support

02/13/2020 07:57 PM - laforge

Status: New	Start date: 02/13/2020
Priority: Low	Due date:
Assignee:	% Done: 0%
Category:	
Target version:	
Resolution:	Spec Reference:
Description The MSC side support for CSD would entail: <ul style="list-style-type: none">• parsing of the "data" bearer type from 04.08 call control• passing it correctly to [external] MNCC• handling incoming "data" bearer from MNCC• permitting data bearer types in intenal MNCC handler• encoding the related channel types in the 48.008 A (ASSIGNMENT CMD, ...)• instructing the MGW to use RTP PT 120 with "CLEARMODE/8000" SDP	
Related issues:	
Related to OsmoBTS - Feature #1572: Circuit Switched Data (CSD) Support	New 02/23/2016
Related to OsmoBSC - Feature #4393: Circuit Switched Data (CSD) Support	New 02/13/2020
Related to OsmoMGW - Feature #4395: Circuit Switched Data (CSD) Support	New 02/13/2020

History

#1 - 02/13/2020 07:57 PM - laforge

- Related to Feature #1572: Circuit Switched Data (CSD) Support added

#2 - 02/13/2020 07:57 PM - laforge

- Related to Feature #4393: Circuit Switched Data (CSD) Support added

#3 - 02/13/2020 07:59 PM - laforge

- Related to Feature #4395: Circuit Switched Data (CSD) Support added