

OsmoMGW - Feature #4395

Circuit Switched Data (CSD) Support

02/13/2020 07:59 PM - laforge

Status: New	Start date: 02/13/2020
Priority: Low	Due date:
Assignee:	% Done: 0%
Category:	
Target version:	
Spec Reference:	
Description CSD support in OsmoMGW would be relatively simple: <ul style="list-style-type: none">• understand the "CLEARTYPE/8000" SDP type as per RFC4040 on the MGCP side• transparently pass the 160 byte per packet payload between endpoints	
Related issues:	
Related to OsmoMSC - Feature #4394: Circuit Switched Data (CSD) Support	New 02/13/2020
Related to OsmoBSC - Feature #4393: Circuit Switched Data (CSD) Support	New 02/13/2020
Related to OsmoBTS - Feature #1572: Circuit Switched Data (CSD) Support	New 02/23/2016

History

#1 - 02/13/2020 07:59 PM - laforge

- Related to Feature #4394: Circuit Switched Data (CSD) Support added

#2 - 02/13/2020 07:59 PM - laforge

- Related to Feature #4393: Circuit Switched Data (CSD) Support added

#3 - 02/13/2020 07:59 PM - laforge

- Related to Feature #1572: Circuit Switched Data (CSD) Support added